UNIVERSAL SERIAL BUS (USB) INTERFACE FOR MASS STORAGE DEVICE

			Also published as:
Publication number:	WO0241154 (A2)		WO0241154 (A3)
Publication date:	2002-05-23		TW275947 (B)
Inventor(s):	HARRIS DAVID H [US]; CLARK GORDON R [US], HOLLAND STEPHEN D [US] +		JP2004536363 (T)
Applicant(s):	CYPRESS SEMICONDUCTOR CORP [US]; HARRIS DAVID H [US]; CLARK GORDON R [US]; HOLLAND STEPHEN D [US] +		AU1783802 (A)
			Cited documents:
Classification:			EP0890905 (A2)
- international:	G06F13/00; G06F13/36; G06F13/38; G06F13/40; G06F3/06; G06F13/00; G06F13/36; G06F13/38; G06F13/40; G06F3/06; (IPC1-7): G06F13/00		US6199122 (B1)
			EP1111498 (A2)
- European:	G06F13/40D5; G06F3/06D		EP0967676 (A2)
Application number:	WO2001US43945 20001116		
Priority number(s):	US20000249530P 20001117		

Abstract of **WO 0241154 (A2)**

A mass storage device motherboard or secondary board includes a bridging circuit. The bridging circuit converts signals from the mass storage device into USB signals. The bridging circuit can be provided by a chip that converts ATA/ATAPI signals into USB signals

Data supplied from the *espacenet* database — Worldwide